

## I-O 2677M Display Module



Display: Supports VGA/SVGA monitors

Columns: 80 column - 960 x 416 or 132 column - 1056 x 435

Sessions: 3 display, 1 printer (DDDP)

Keyboard: 102/103-key (standard), 122-key (optional), low profile, adjustable height, tactile keys

Approvals: Display Module: FCC Part 15, Energy Star, CE  
Power Supply: UL, CSA, CE, Baurt

Power: 100-250 VAC 47-63 Hz Auto-ranging

Environment: +32° to 105° F (0° to +40° C)

The I-O 2677M\* Display Module is a low cost, modular midrange display device which is compact and fully featured. The I-O 2677M includes the display module, a 102/103-key or 122-key keyboard, and a universal power supply. The I-O 2677M provides outstanding benefits such as:

- Low Cost - No special software or training required
- Exclusivity - Exclusive features such as Twinax Monitor Mode
- Multi-Session - Four session (DDDP) multi-task functionality
- Compact Design - Requires minimal space
- Printer Port - Printing flexibility at a very low cost
- High Resolution - Sharp, easy-to-read characters

The I-O 2677M includes a Manufacturer's Three Year Limited Warranty to further reduce cost of ownership. For all these reasons we think you'll agree . . . the I-O 2677M is the price/performance leader in midrange display modules and is an alternative display device for those who are not quite ready for a network computer.

\* Monitor not included.

### IBM Features:

Attaches to:

IBM AS/400, System/36, /38, 5294, 5394, 5494, and I-O 8294, 8394, 8394E, 8394Ei and 8494 series remote controllers.

Multiple Sessions: 3 Display + 1 Printer

Multiple Emulations: 3180, 3196, 3197C & D, 5251-11, 5291, 3487C Non Info Window

Host Addressable Printer Port

Multiple Language Support:

US/Canadian English, UK English, Austrian/ German, Swiss-German, French (AZERTY), Belgian (AZERTY), Swiss-French, Canadian French, Italian, Spanish, L/A Spanish, Portuguese, Swedish, Finnish, Danish, Norwegian, Dutch, and Multinational

Standard PC Parallel Printer Connector

Dual Cursors, Rule Cursor

Tilt and Swivel Capability

Auto Terminating Twinax "V" Cable

### Plus a wide range of additional features that boost productivity and performance.

Features	Benefits
VESA-DPMS Power Saver Mode	Reduces power consumption on the monitor.
Horizontal Split Screen	80/80, 80/132, 132/132 modes for multi-task operation.
Multiple Printer Emulations	5224, 5225, and 5256 emulations allow flexible, low cost printing.
Laser Printer Support	Any HP compatible PCL4 or PCL5 laser printer may be attached.
Printer Control from Keyboard	New Line, Form Feed, Stop, Start, and Cancel are all available from the keyboard.
I-O Command Pass-Thru™	Allows control of all user-programmable features of the printer.
Local Screen Print	Local print copy at any time.
Record/Pause/Play Function	Up to 1,570 keystrokes of Record/Pause/Playback past enter with security options.
Overscan/Reverse Video	Reverses the background and text of the screen.
Software Security	Blanks the screen and inhibits input from the keyboard without signing off the display.
Printer Code Editor	Allows customization of printer tables which provide attachment to various printers.
Twinax Monitor Mode	Diagnostic tests that indicate what is occurring on the twinax cable.